

Electrical Adapter

Background of the Invention

5 The present invention relates to main power electrical connectors. More particularly, although not exclusively, the invention relates to a main power electrical adapter having a choice of configurations.

10 Electric plugs for insertion to wall sockets are of course known. These either comprise two or three pins, depending upon whether an earth pin is needed. The plugs have a power cord extending therefrom, usually directly outwardly from the wall, or otherwise in a direction

15 parallel to the wall in a downward or downward and angularly-offset manner. Sometimes this pre-set angle at which the power cord extends from the plug body is inconvenient. For example, when the cord extends normally to the wall and it is desired to place furniture

20 against the wall at that position, the furniture must often need to be spaced from the wall. If the power cord is short and extends downwardly from the plug when the plug is inserted into the wall socket, this can create problems where say it extends from a desk lamp for

25 example to be positioned at a higher level than that of the wall socket. In such a situation, it would be more appropriate that the plug have the power cord extending upwardly instead of downwardly therefrom.

Also, the pin configuration of wall sockets and electrical plugs vary from country to country. When travelling with a laptop computer for example one often
5 has to carry traveller's adapters. These can be bulky, cumbersome items.

Objects of the Invention

10 It is an object of the present invention to overcome or substantially ameliorate at least one of the above disadvantages and/or more generally to provide an improved electrical adapter.

15 Disclosure of the Invention

In one form, the invention comprises an electrical adapter for use in countries having mains electrical pin/socket patterns that allow no alternative plug-insertion
20 orientations, comprising:

a base having electrical terminals and engagable pivot connection features, and

a body having engager pivot connecting features for co-operating with the engagable pivot connection features
25 of the base to secure the body rotatably to the base in one of only two possible orientations - one of which 180 offset with respect to the other, the body having electrical contacts configured to engage with the

terminals of the base when the body and base are so secured.

In another form, the invention comprises an electrical
5 adapter comprising:

a base having electrical terminals and engagable bayonet connection features, and

a body having engager bayonet connecting features for co-operating with the engagable bayonet connection
10 features of the base to secure the body rotatably to the base, the body having electrical contacts configured to engage with the terminals of the base when the body and base are so secured.

15

In a further form, the invention comprises an electrical adapter comprising:

a base having electrical terminals and engagable pivot connection features,

20 a body having engager pivot connecting features for co-operating with the engagable pivot connection features of the base to secure the body rotatably to the base, the body having electrical contacts configured to engage with the terminals of the base when the body and base are so
25 secured, and

a locking device by which the body is automatically locked to the base when pivotally interconnected therewith, but that requires manual depression to unlock

the body from the base.

Preferably the base has conducting pins extending from one side thereof for insertion into apertures of a mating
5 socket and the electrical terminals are located on the other side of the base and correspond to each of the conducting pins and are connected electrically thereto.

Alternatively the base can have extending therefrom
10 another power cord at a remote end of which there is a plug having conducting pins for insertion into apertures of a mating socket and wherein the electrical terminals are connected electrically to each of the conducting pins via individual conductors in said another power cord.

15

Preferably the engagable and engager pivot mounting features are mutually bayonet-inter-engagable.

Preferably the engagable pivot mounting features of the
20 base comprise a number of radially extending lugs having circumferentially extending ramp surfaces.

Preferably the engager pivot mounting features of the body comprise openings through which the lugs must pass for
25 interengagement of the base and the body to take place.

Preferably said lugs are of differing size and said openings are of corresponding differing size to restrict

allowable alignment orientations of the body and base when interconnected.

Preferably the base comprises an annular channel within
5 which the terminals are located.

Preferably the terminals are located within narrowed parts of the channel.

10 Preferably the body includes a locking device by which the base is locked to the body when interconnected therewith.

Preferably the electrical contacts of the body are spring-biased toward the terminals.

15

Preferably the electrical contacts of the body are connected to individual conductors of a power cord extending from the body.

20 Brief Description of the Drawings

A preferred form of the present invention will now be described by way of example with reference to the accompanying drawings, wherein:

25

Figure 1 is a schematic perspective illustration of the base,

Figure 2 is a schematic inverted perspective illustration of the base,

Figure 3 is a schematic perspective illustration of a
5 body for connection to the base of Figures 1 and 2,

Figure 4 is a schematic perspective detailed illustration of parts of the body of Figure 3,

10 Figures 5 and 6 are schematic perspective illustrations of the body and base showing the base in its alternative insertion orientations,

Figures 7 and 8 are schematic perspective illustrations
15 of the body and base with the base illustrated in alternate locked orientations, and

Figure 9 is a schematic perspective illustration of an alternative base having an extension cord extending
20 therefrom with a plug at its remote end.

Description of the Preferred Embodiment

In the accompanying drawings there is schematically
25 depicted an adapter base 10 and a mating plug body 20.

Figures 1 and 2 depict the adapter base 10. The adapter base 10 is fabricated typically as a moulding of plastics

material and includes a plate 13 having three projecting
metallic electrically conductive pins projecting from one
side. There are active and neutral pins 11 and an earth
pin 12. Alternatively, there might simply be a pair of
5 active and neutral pins. As yet a further alternative,
the pin 12 might be a plastics or other non-conductive
dummy pin. The adapter base 10 of the illustrated
embodiment has its pins configured in the standard
British layout, but it should be appreciated that the pin
10 configuration could equally be that of Australia, the
USA, or any other country. Indeed, the plug body 20 of
Figures 3 and 4 might be supplied with a number of bases
10, each base having a configuration applicable for a
different country.

15
At the other side of the plate 13 there is provided a
flat bearing ring 14 formed as an integral moulding
therewith. Located internally and concentrically with
the bearing surface 14 is an inner circular projecting
20 rail 7 and an outer circular rail 15. Between the two
rails there is defined an annular channel 9 having a
pair of diametrically opposed narrowed portions 8. At
the bottom part of each narrowed portion 8 there is
provided a terminal 17. One of the terminals is
25 connected electrically with either the active or neutral
pin 11 and the other terminal is connected to the other
pin 11. There might also be a further terminal 17
connected with the earth pin 12.

The outer rail 15 has extending therefrom four bayonet lugs 16. Each bayonet lug 16 is spaced from the bearing surface 14 and includes a circumferentially extending
5 ramped upper surface. Diametrically opposed pairs of the bayonet lugs 16 are of the same size, yet adjacent pairs of the bayonet lugs are of differing size.

Figures 3 and 4 depict a plug body 20 for bayonet-inter-
10 connection with the adapter base 10. The plug body 20 is typically fabricated from several plastics moulded parts that are screwed, snapped or welded together ultrasonically and has extending from it via a rubber grommet 22 a power cord 21.

15

The plug body 20 includes a flat circular bearing ring 33 for engagement with the bearing ring 14 of the adapter base 10. There is a central recess 32 in which there is located a pair of diametrically opposed electrical spring
20 contacts 26. These spring contacts are connected electrically with individual conductors within the cord 21. Located around the central recess 32 there are four openings 31. Diametrically opposed pairs of the openings 31 are of the same size, whereas adjacent pairs are of
25 different size. By this arrangement, bayonet lugs of the adapter base 10 can be lowered into the openings 31 of the plug body 20 in only two possible orientations, namely those as depicted in Figures 5 and 6 respectively.

That is, the openings 31 are just large enough to receive the lugs and the larger pair of the four lugs will not fit into the smaller openings.

- 5 Alongside each opening 31 and situated beneath the bearing ring 33 are lug-receiving slots 29. There are ramp surfaces at the bottom of each opening 31.

10 Situated alongside and projecting within one of the openings 31 is a locking device comprising an interlock tongue 24 and an activator 23 formed integrally therewith. The tongue 24 projects into a tongue recess 25 as depicted in Figure 4. With reference again to Figure 1, the outer rail 15 includes a pair of

15 diametrically opposed interlock recesses 18 into one of which the tongue 24 snap-engages upon bayonet-fitting of the two components. The activator 23 is an integral part of the plug body 20 and has a pair of cut-outs at either side enabling downward movement of the interlocked tongue

20 24 upon application of finger-pressure to the activator 23. It is only upon this application of finger pressure that the interlocked parts can be detached.

25 In use, parts 10 and 20 are attached as shown in Figure 5 and 6 and then the adapter based 10 is rotated clockwise until the bayonet lugs bear against end walls 28 at each slot 29. At this time, the interlock tongue 24 snaps into one of the interlock recesses 18, depending upon the

chosen orientation as depicted in either of Figures 7 or 8. The attached components can then be plugged into a wall socket, plug board, or extension cord for example.

5 There is an alignment indicator 30 on the plug body 20 and a corresponding pair of indicators 34 on the adapter base to assist in aligning the components as illustrated in Figures 5 and 6.

10 It should be appreciated that modifications and alterations obvious to those skilled in the art are not to be considered as beyond the scope of the present invention. For example, there might be located within the plug body 20 a transformer to provide a low voltage
15 output to the power cord 21. Also, instead of a bayonet-type interengagement, other types of plug-in arrangements might be adopted.

Furthermore, it is envisaged that the base of the
20 electrical adapter need not be configured with pins to be received directly by apertures of a mating socket. For example, and as shown in Figure 9, the base might have an extension cord 35 extending therefrom and at the remote end of which there is a standard plug 36 to be
25 received by a wall socket or another extension cord for example.

Also, the body might be formed integrally with an

electrical appliance, double adapter, multiple plug board, transformer box or the like.